

SL86

Rugged Pad



Headquarters:
Datavägen 21B
SE-436 32 Askim, Sweden
info@satlab.com.se

Regional Offices:
Warsaw, Poland
Jičín, Czech Republic
Ankara, Turkey
Scottsdale, USA
Singapore
Hong Kong, China
Dubai, UAE

www.satlab.com.se

SL86 Rugged Pad

Data Specifications

SYSTEM

Operating System	Android 9.0
CPU	MSM8953 Octa-core (2.0GHz)
GPU	Adreno 506 1920 x 1200 @ 60 fps
Supported Capacity RAM	4GB DDR3
ROM	64GB
G Sensor	Gravity Accelerator Sensor
Sensors	Compass, Gyroscope
Audio Features	1x internal microphones, 1x built-in speakers
Integrated WLAN	WLAN 802.11 a/b/g/n
GNSS Features	GPS: L1 C/A GLONASS: L1 FDMA

Bluetooth Network	Bt4.1 (BLE) Class 1 Transmission Distance: 10m 3G/4G
-------------------	---

MULTI-MEDIA

Camera	Front Camera: 2.0 megapixel Rear Camera: 13.0 megapixel
--------	--

DISPLAY

Screen	8 inch (10:16) Gorilla Glass TP
Brightness	Minimum 700cd/m ²
Resolution	800 x 1280

INTERFACE CONFIGURATION

Ports	USB 2.0 TF Slot, HDMI 1.4a, Micro SIM Slot 12pin Pogo Pin DC Connector 3.5mm Standard Earphone Jack
-------	---

ACCESSORIES

Standard	OTG Cable Type-C Cable Power Adaptor: AC100V - 240V 50Hz/60Hz output (DC 5v/3A)
Optional	Docking Charger, Car Holder, Straps

GENERAL

Environmental	IP67/MIL-STD-810G Humidity 95% (non-condensing) Drop resistant to 1.2m Temperature -10°C to 50°C Operation -30°C to 70°C Storage
---------------	--

Physical Properties

Size: 228mm x 145mm x 16.5mm
Weight: 715g
Battery Capacity: 3.7V/ 8500mAh