

SL86

Rugged Pad



CE



Made by Sweden

SL86 Rugged Pad

Data Specifications

SYSTEM

Operating System	Windows 10	Android 10.0
CPU	Intel® Cherry Trail Z8350 (1.44 Ghz - 1.92 Ghz)	MSM8953 Octa-core (2.0 GHz)
GPU	Intel® HD Graphics	Adreno 506
Supported Capacity RAM	2 GB/4 GB DDR3	4 GB DDR3
ROM	64 GB	64 GB
G Sensor	Gravity Accelerator Sensor	Gravity Accelerator Sensor
Sensors	Compass, Gyroscope	Compass, Gyroscope
Audio Features	1x internal microphones, 1x built-in speakers	1x internal microphones, 1x built-in speakers
Integrated WLAN	WLAN 802.11 a/b/g/n	WLAN 802.11 a/b/g/n
GNSS Features	56 Channel, U-Blox7 Engine GPS: L1 C/A GLONASS: L1 FDMA QZSS: L1 C/A SBAS: WAAS, EGNOS, MSAS	GPS: L1 C/A GLONASS: L1 FDMA
Bluetooth	BT4.1 (BLE) Class 1 Transmission Distance: 10 m	BT4.1 (BLE) Class 1 Transmission Distance: 10 m
Network	3 G/4 G	4 G

MULTI-MEDIA

Camera	Front Camera: 2.0 megapixel Rear Camera: 5.0 megapixel	Front Camera: 2.0 megapixel Rear Camera: 13.0 megapixel
---------------	---	--

DISPLAY

Screen	8 inch (10:16) Gorilla Glass TP	8 inch (10:16) Gorilla Glass TP
Brightness	320 cd/m ²	700 cd/m ²
Resolution	800 x 1280	800 x 1280

INTERFACE CONFIGURATION

Ports	USB 2.0 TF Slot, HDMI 1.4a, Micro SIM Slot 12pin Pogo Pin DC Connector 3.5 mm Standard Earphone Jack	USB 2.0 TF Slot, HDMI 1.4a, Micro SIM Slot 12pin Pogo Pin DC Connector 3.5 mm Standard Earphone Jack
--------------	--	--

ACCESSORIES

Standard	OTG Cable USB Cable Power Adaptor: AC100 V - 240 V 50 Hz/60 Hz output (DC 5 V/3 A)	OTG Cable Type-C Cable Power Adaptor: AC100 V - 240 V 50 Hz/60 Hz output (DC 5 V/3 A)
Optional	Docking Charger, Car Holder, Straps	Docking Charger, Car Holder, Straps

GENERAL

Environmental	IP67/MIL-STD-810 G Humidity 95% (non-condensing) Drop resistant to 1.2 m Temperature: -10°C to 50°C Operation -30°C to 70°C Storage	IP67/MIL-STD-810 G Humidity 95% (non-condensing) Drop resistant to 1.2 m Temperature: -10°C to 50°C Operation -30°C to 70°C Storage
----------------------	---	---

Physical Properties

Size: 225 mm x 143 mm x 19 mm	Size: 228 mm x 145 mm x 16.5 mm
Weight: 740 g	Weight: 715 g
Battery Capacity: 3.7V/8500 mAH (3 G)	Battery Capacity: 3.7V/ 8500 mAH
3.7V/7800 mAH (4 G)	



Headquarters:
Datavägen 21B
SE-436 32 Askim, Sweden
info@satlab.com.se

Regional Offices:
Warsaw, Poland
Jičín, Czech Republic
Ankara, Turkey
Scottsdale, USA
Singapore
Hong Kong, China
Dubai, UAE

www.satlab.com.se

